

# TECHNICAL DATA SHEET

## 3B – 36KG GLASS FIBRE BONDING

Issue2 – October 2015

**Definition:** Manufactured using a glass fibre tissue with oxidised bitumen. It is intended for use in built-up felt roofing using traditional roll and pour bonding.

**Composition and Manufacture:** The base carrier consists of 60g/m<sup>2</sup> plain glass tissue. The carrier material is coated both sides in a continuous operation using oxidised bitumen. The coated material is finished with fine sand both sides. The material is cut to roll length, wrapped and labelled according to specification.

**Storage and Handling:** Do not drag rolls across rough surfaces, they should be lifted. Rolls should be stood on their ends on a dry surface. If using pallets do not stack more than two pallets high without using a pallet board. Avoid mechanical damage and damp storage conditions.

**Technical Data:**

Product	3B - 36KG Glass Bonding
Carrier	Plain Glass Tissue
Roll Size	20m x 1m
Roll Weight	36kg
M <sup>2</sup> Weight	1.8kg
Rolls Per Pallet	25

**Health and Safety:** Please refer to the Health and Safety Data Sheet on 3B Glass Fibre Bonding.

**Further Information:**

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.