

TECHNICAL DATA SHEET CREOTREAT

Issue 5 - October 2015

Description: An oil based timber treatment and stain for outside use on fences, sheds and timber posts.

Colour: Dark Brown, Light Brown + Black

Method of

Application: By Brush

Container Sizes: 4, 25 and 200 litres

Directions for Use: Colours may vary, check prior to use. Do not dilute. For outside use only. Tighten cap after

use. Untreated timber requires no special treatment. Old timber fences should be free of dirt,

moss and fungal growth. Use stiff brush and apply to dry surfaces.

Coverage Rates: 1 - 4m² per litre per coat.

Technical Data:

Typical Properties	
Density @ 20°C	1.010
Water Content (Maximum - %v/v)	1.5
Flash Point °C (minimum by Pensky-Martens	85
Closed Cup)	
Tar Acids (phenolic compounds)	Trace
Liquidity after 48 hours at -15°C	Liquid
Distillation:	
5% distilled at (°C):	205
80% distilled at (°C):	370

Cleaning Tools: Tools may be cleaned with White Spirit.

Storage Life: Storage life indefinite in tightly sealed, undamaged containers.

Health & Safety: Please refer to health and safety data sheet on Creotreat

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com