

TECHNICAL DATA SHEET

HAND HELD FOAM

Issue 5 – December 2012

Description:

An easy to use, polyurethane based expanding foam for general construction and home improvement applications.

Uses:

Filling large, irregular or awkward gaps where the foam will expand to completely fill the cavity. Fixing window frames, loose tiles and boards. Insulating between brickwork and cladding around ductwork and through cavities carrying pipes and cables. Can be used as a backing material to fill large joints before over-sealing.

Colour:

Green

Packaging:

12 x 750ml Canisters per box

12 x 500ml Canisters per box

Preparation:

Ensure surfaces to be treated are free from grease, dust and loose material. **IMPORTANT** – moisten surfaces well before use as this improves adhesion and finished cell structure of the foam.

Application:

Method

Shake the can intensively at least 20 times prior to use. Remove cap and screw the adapter firmly onto the valve. To apply foam turn the can upside down and press the adapter. Only use in temperatures of +5°C to +35°C.

Filling

Half fill the cavity and lightly spray the foam with water. The foam will expand to fill the rest.

Fixing

When fixing window frames use wedges to hold the frame in place until the foam is fully cured – approximately 24 hours.

Finishing:

Can be cut, sawn, plastered or painted when cured. It is the user's responsibility to dispose of all packaging correctly.

Cured PU Foam can only be mechanically removed.

Limitations:

Care should be taken to protect surrounding surfaces. When exposed to sunlight apply sealant or render within 7 days as the foam is not resistant to ultra violet light. Not suitable for use on silicone, Teflon, polyethylene, and greasy or oily surfaces. Compatibility tests are recommended prior to application. It is the user's responsibility to determine suitability.

Technical Information:

Technical Data	Gun Grade Foam
Base	Polyurethane
Application Temperature	+5°C - +35°C
Temperature of can during application	Min +10°C
Density (ISO 7390)	19 – 35kg/m ³
Skinning Time*	10 – 15 min
Cutting Time*	60 – 100 min
Curing Time*	5 – 24 hours
Freeze Resistance	Up to -15°C during transportation
Temperature Resistance	-40°C - +90°C
Insulation Value	25 – 30mW/mK (DIN 52612)

*Under laboratory conditions at the temperature of +23°C; U.R. 55%

Precautions:

Use in well ventilated area away from all sources of ignition, including pilot lights. Protect skin during use. Always wear gloves and safety glasses. Wear suitable workwear. Cover carpets and household furnishings before use. Keep out of reach of children. Keep out of reach of children. Follow instructions carefully.

Liability:

The information given is the result of our tests and experience and is believed to be accurate and reliable. However as Cromar Building Products Limited cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use.

Storage:

Always store upright in cool, dry conditions. Do not expose to temperatures above +50°C.

Health & Safety:

Please refer to health & safety data sheet on Hand Held Foam.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com