

TECHNICAL DATA SHEET

HI-BOND PRIMER

DESCRIPTION:

Cromar Hi-Bond Primer is an acrylic co-polymer emulsion used to treat vertical and horizontal surfaces prior to applying mastic asphalt.

USES:

Priming of concrete surfaces to accept mastic asphalt top coating.

DIRECTIONS FOR USE:

Ensure that the surface is sound, clean, and free from moss, lichen etc.

Apply using brush or roller.

Allow to dry thoroughly before applying mastic asphalt.

COVERAGE

Approx. 5m² per lt. on concrete.

CLEANING

Clean tools with water immediately after use.

PACKAGING:

5lt and 20lt plastic pails.

COLOUR

Orange, drying to translucent.

STORAGE

Store in unopened, original packaging between +5°C and +25°C in dry conditions.

SHELF LIFE

Up to 1 year if stored as recommended above.

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as

the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com