

TECHNICAL DATA SHEET

MOULD RELEASE OIL

Issue 2 – November 2015

- Description:** Mould Release Oil can be applied to timber, steel and plastic faced moulds or shutter faces. Reacting chemically with cement at the surface it ensures the quick, clean release of the hardened concrete. It produces a uniform hard finish which is light in colour and does not stain even white cement. When grained effect is required Cromar Mould Release Oil can be applied to rough-sawn timber.
- Advantages:** Improves release performance compared with oils and creams and reduces occurrence of blow holes.
Economical – only a light film required.
Waterproofs plywood and timber moulds preventing the wood swelling and ensuring even hydration.
- Directions for Use:** Coverage varies with the porosity of the surface and method of application but a rate of 20m²/litre can be expected.
- Storage:** Store in a cool, dry, well ventilated space.
Keep in a cool, dry, well ventilated place
Keep away from direct sunlight.
Keep away from heat and sources of ignition
Keep only in original container.
The shelf life for this product is 12 months.
- Packaging:** 5 & 25 litres
- Health and Safety:** Please refer to Health and Safety Data Sheet on Mould Release Oil.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.