

TECHNICAL DATA SHEET B LOCK & PAVING SEALER

Issue 5 – January 2012

Description:

Block & Paving Sealer is an effective protection of block pavers and masonry.

Use:

Block & Paving Sealer provides a durable penetrative sealer to a wide variety of materials including concrete, screeds, brickwork, masonry and fibrous sheet materials. The use of Block & Paving Sealer helps provide protection to both new and existing concrete and masonry against water and air borne pollutants.

Advantages:

1. Can be applied to green concrete (after 4 – 6 weeks)
2. Non-yellowing
3. Dual Sealer and Curing Action
4. High Penetration
5. Suitable to receive subsequent treatments
6. Can be used on horizontal or vertical surfaces
7. Vapour permeable allowing the substrate to breath
8. Provides increased protection to atmospheric gases including carbon dioxide.

Mixing:

Block & Paving Seal is supplied ready for use.

Method of Application:

By brush, roller or spray.

Directions:

All surfaces must be dry and sound and free from any oil, grease, treatment debris and algae. New concrete must be left for 4 to 6 weeks prior to treatment. Do not apply if rain is likely within 3 to 4 hours of application. Apply to a small test area if in doubt and leave for 24 hours. Apply by brush or roller, work well into the surface taking care not to brush out jointing sand. Apply one or two coats dependent on desired effect. Allow 2 to 3 hours between coats. Product must be left at least 48 hours to fully cure before the treated area can allow any form of traffic. Clean equipment with soapy water.

Dilution:

Shake or stir container before use.

Container Sizes:

1, 2.5, 5 & 25 litres

Coverage Rates:

Coverage will depend on the porosity of the substrate. Guideline coverage is 6m² per litre.

VOC Details:

EU Limit for this product CAT. 2(h) : 30g/l (2010). This product contains max. 0g/l VOC's.

Storage:

Store in a cool dry place away from direct heat or naked flame. Containers should be tightly closed.

Limitations

Do not use on Indian Stone.

Health & Safety:

Please refer to Health & Safety Data Sheet for Block & Paving Sealer

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com