

## TECHNICAL DATA SHEET – CromaVerge, the Premium Universal Dry Verge

### DESCRIPTION:

Dry Verge Systems provide a reliable and sturdy approach to affixing interlocking tiles, eliminating the need for mortar. Ranging from convenient individual dry verge caps that effortlessly interlock to a seamless continuous dry verge system for a sleek appearance, we deliver comprehensive verge solutions.

Universal quick and easy to install dry verge system that does not require separate left hand and right-hand units. This system is maintenance free, cost effective and supersedes the traditional mortar for pointing the verge.

### MATERIAL:

PP Grey UV 20% MF Compound Type 16006

### FEATURES:

A premium, universal dry verge system, no need for separate left or right-handed verges. Available in 4 popular colours, angled and rounded ends caps to match to suit.

- Universally handed – no need for left and right units
- Quick fit design – 36 units in under 5 minutes
- Versatile – fit to any type of roof tile
- High compression – roof tiles held firm in strong winds
- Zero maintenance – years of mortar free protection
- High quality – tough and UV stable plastic
- Mortar free – eaves remain protected but well ventilated



### **RECOMMENDED PARTS LIST:**

(Items Available Separately)

- Verge unit
- Eaves Starter Kit
- Ridge End Cap (half round and angled)

### **PACKAGING:**

Packaged in boxes of 60

### **LIMITATIONS:**

Performance independently tested to BS8612

Helps to meet BS5534 code of practice for slating and tiling

### **Further Information:**

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.