

# TECHNICAL DATA SHEET

## CROMAPOL SCRIM

### DESCRIPTION:

Reinforcement Scrim for liquid applied roof coatings

Cromapol Scrim is a 100% fibreglass scrim fabric, and is coated with a weavelock, in order to give the fabric dimensional stability.

### PRODUCT SPECIFICATIONS

Weight	58 gr/m <sup>2</sup>
Thickness	0.20 mm
Construction	Setting/cm : 3.8 x 3.9
Warp/tex	EC9 - 2 x 34
Weft/tex	EC9 – 68
Tensile strength	(warp x weft) 85 x 75 daN / 5 cm
Weave	Leno
Visual mesh	10 x 10 (openings per sq. inch)
Max. application temperature	300°C
Fire classification	M-0

### COVERAGE:

50 m<sup>2</sup> per roll

### PACKAGING:

Roll size: - 100 cm x 50 m (50 m<sup>2</sup> per roll)

### Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.