

TECHNICAL DATASHEET

Multi Finish Plaster

Description & Uses

Cromar AlphaChem Multi Finish Plaster is a pre-blended anhydrite based finishing plaster which applies in the same way as a traditional backing plaster but closes and finishes like a first class finishing plaster. Produces a hard and durable impact resistant plaster that leaves a smooth natural looking finish in just one coat. CE marked to EN13279-1:2008.

Suitable for plastering over most traditional materials.

Part of the AlphaChem Small Bag range of products – ideal for small jobs, meaning less wastage. The plastic sealed bags also mean the product is kept fresher for longer.

Application

- Ensure all contact surfaces are clean and dust free.
- Add AlphaChem Multi Finish Plaster to container containing 1.5-2 litres of clean, cool water and mix to desired working consistency using a drill and mortar paddle.
- For best results, allow the mixed plaster to rest for 3-5 minutes to enable the plaster to “fatten up”, then mix again, adding more water if necessary.
- Multi Finish Plaster should be applied at nominal thickness of 10mm.
- It is the user’s responsibility to dispose of all packaging correctly.

Storage

Store indoors in cool, dry conditions between +5 and +25°C. Protect from frost.

Shelf Life

12 months if stored as directed in original, sealed packaging.

Limitations

- Not suitable for wet area or areas of high humidity.



- It is the user's responsibility to ensure suitability for use.
- Read the label prior to use it contains essential health and safety information, further information can be found on the Safety Data Sheet available on request.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.