

# TECHNICAL DATASHEET

## ORANGE HEAVY DUTY GAFFA TAPE

### Description & Uses

Cromar AlphaChem Orange Heavy Duty Tape has an ultra-high tack adhesive formulated to ensure that one strip is all that is needed. The adhesive will adhere to polythene, plaster, brick, concrete, aluminium and steel and will perform at both high and low temperatures.

Ideal for:

- Bonding, protecting, joining, bundling, repairing, patching etc.
- Applications where strong vertical hold properties are required.
- All applications within the demanding building and construction industries.

### Directions

- Ensure all surfaces are clean, sound and dry.
- Remove the outer packaging from the orange tape.
- Peel the amount of tape required and apply.
- Finish by either tearing or cutting when finished.

### Storage

Store in cool, dry conditions between +5°C and +25°C.

### Limitations

- If using a knife to cut the tape, ensure to be careful of the blade – use responsibly.
- It is the user's responsibility to ensure suitability for use.

### Technical Data



<b>Total thickness</b>	0.26mm
<b>Adhesion to Steel</b>	8.76 N/cm
<b>Adhesion to Backing</b>	5.47 N/cm
<b>Tensile Strength</b>	42.03 N/cm
<b>Maximum Performance Temperature</b>	-10°C up to +93°C
<b>Flame Spread</b>	10
<b>Smoke Developed</b>	5

**Further Information:**

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

*All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.*