

TECHNICAL DATASHEET

Rapid Set Mortar

Description & Uses

Cromar AlphaChem Rapid Set Mortar is formulated from Ordinary Portland Cement and Kiln Dried Silica sand as well as specially selected additives to make the mortar workable, fast setting and hard wearing. Initial set occurs within approximately 10 minutes, dependent on ambient temperature, final set within 30 minutes.

When mixed together with water it creates the perfect mix for small repair jobs such as filling holes in brick and block work and pointing repairs.

Part of the AlphaChem Small Bag range of products – ideal for small jobs, meaning less wastage. The plastic sealed bags also mean the product is kept fresher for longer.

Application

- Mix contents of bag on a board or in a bucket with water using a trowel, add water slowly until you have a consistency you are happy with for the job you're doing.
- Be careful not to get your mix too wet!
- It is the user's responsibility to dispose of all packaging correctly.

Storage

Store indoors in cool, dry conditions between +5 and +25°C in airtight container. Protect from frost.

Shelf Life

12 months if stored as directed in original, sealed packaging.

Limitations

- Do not use during freezing conditions.
- Do not use in extreme heat (above 30 degrees).
- Care must be taken if used in conjunction with ceramics as slight expansion will occur during the setting process i.e. fixing sanitaryware.
- It is the user's responsibility to ensure suitability for use.



- Read the label prior to use it contains essential health and safety information, further information can be found on the Safety Data Sheet available on request.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.