

TECHNICAL DATASHEET

Mould release Oil

Description & Uses

Mould Release Oil can be applied to timber, steel and plastic faced moulds or shutter faces. Reacting chemically with cement at the surface it ensures the quick, clean release of the hardened concrete. It produces a uniform hard finish which is light in colour and does not stain even white cement. When grained effect is required Cromar Mould Release Oil can be applied to rough-sawn timber.

Benefits

- Improves release performance compared with oils and creams and reduces occurrence of blow holes.
- Economical – only a light film required.
- Waterproofs plywood and timber moulds preventing the wood swelling and ensuring even hydration.

Directions

Coverage varies with the porosity of the surface and method of application but a rate of 20m²/litre can be expected.

Storage

Store in a cool, dry, well ventilated space. Keep in a cool, dry, well ventilated place. Keep away from direct sunlight. Keep away from heat and sources of ignition. Keep only in original container.

Shelf Life

12 months when stored in original, unopened packaging.

Limitations

- It is the user's responsibility to ensure suitability for use. Safety Data available on request.
- Read the label carefully for essential health and safety information prior to use.

Technical Data

Solubility	Soluble in most organic solvents
Relative Density	0.82 – 0.88
Flash Point	>55 C
Colour	Red

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.