

TECHNICAL DATASHEET

Patination Oil

Description & Uses

Specially developed to reduce unsightly staining due to white carbonate and to impart a pleasing appearance to newly applied lead sheet and flashings. It has been specially formulated to provide a protective film coating enhancing the lead colour. Suitable for all external applicational to lead-work.

Application Instructions:

- All lead to be treated should be clean, dry and free from dust and debris.
- Cromar Patination Oil should be applied after each step of the lead work, and completed by the end of the day.
- Shake the container for at least 2 minutes prior to use.
- Apply with a soft absorbent cloth, working horizontally and top to bottom.
- Ensure the application is complete prior to any rain.

Coverage Rates

Approx. 60m² per litre.

Cleaning

Brushes etc can be cleaned with White Spirit followed by detergent.

Storage Conditions

Containers should be stored in a cool, dry, well ventilated place away from sources of ignition at between 5°C and 30°C. Keep out of direct sunlight.

Shelf Life

The product has a 12 months shelf life subject to correct storage.

Limitations

-
- Do not allow Patination Oil to come into contact with bitumen and polycarbonate surfaces.
- It is the user's responsibility to ensure suitability for use. Safety Data available on request.
- Read the label carefully for essential health and safety information prior to use.



Technical Data

Appearance	Brown/Gold Liquid
Flash Point	38 ° C
Specific Gravity	0.78
Application Temperature	+5 ° C to 30° C
Temperature range serviceable at	-20 ° C to +40 ° C
Initial Cure	12 hours @ 20 ° C

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.