

TECHNICAL DATA SHEET

Decking Oil

Issue 2 – October 2015

Description: Cromar Decking Oil is specially designed to be used on timber decking to enhance the beauty of the wood, and to help protect against drying and splitting. It also helps protect against water penetration which can cause warping and swelling.
Cromar Decking Oil should be dry within 24 hours of application.
It can be used on all types of decking including pre-treated, pressure treated or preservative-impregnated timber.
It is available in Clear, Cedar, Oak and Pine shades to match or alter the colour of your decking.

Preparation: Decking timber must be free from dust, dirt mildew mould and other contaminants. To achieve this, a thorough washing with Cromar Decking Cleaner is recommended. Allow decking to dry thoroughly before continuing.

Application: **Do not apply in wet conditions, or if rain or frost are expected before the product is dry.** Ensure that the cap is firm and shake container vigorously to thoroughly mix contents. **Do not dilute.** Apply to the prepared surface two liberal coats of Cromar Decking Oil (chosen colour) by brush or roller, ensuring saturation of joints and end grain. Allow to become touch-dry between coats. (Approx 2-4 hours depending on ambient temperature) Decking should be dry and ready for use after 24 hours.

N.B: Please note that the final colour, when dry, will depend on the type of wood to which it is applied and whether any previous application of coloured preservative has been made. In such instances, we recommend a test area to ensure that the finished result is acceptable.

Container Sizes: 5, 25

Coverage Rates: This is greatly dependent on the type of timber being treated, but as a rough guide coverage will be 4 to 6m² per litre for each coat.

Cleaning: Brushes etc. can be cleaned with White Spirit followed by detergent.

Storage Conditions: Containers should be stored out of direct sunlight in dry conditions away from sources of ignition. They should be stored undercover below a temperature of 35°C.

Health & Safety: Please refer to health and safety data sheet on Cromar Decking Oil

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com