

TECHNICAL DATA SHEET

DECKING SEALER

Issue 2 – October 2015

Description:

Cromar Decking Sealer is a quality clear sealer formulated to provide an effective water repellent barrier for the protection of timber decking. Cromar Decking Sealer will waterproof and protect any smooth or ridged, hardwood or softwood decking timber including pressure-treated, pre-treated or preservative impregnated timber. Cromar Decking Sealer helps to prevent drying, wetting, swelling, splitting and cracking of the timber, but still allowing the surface to breathe and moisture inside the wood to evaporate.

Preparation:

Ensure that the decking timbers are completely dry and free from any dust, dirt, lichen, oil etc. prior to application. Remove all existing loose and flaking stains. Do not use detergents to clean down the substrate.

Application:

A test patch is always recommended, prior to use to ensure desired result is achieved.

Do not apply in wet conditions or if rain or frost is likely before the product is completely dry
Pour Cromar Decking Sealer into a suitable container. Apply liberally 2 coats leaving 24 hours between coats using a brush, roller or low pressure spray.

Very porous timber may require a third coat.

On horizontal timber decking remove puddling by redistributing to dry areas after 15 minutes.

Do not spray on any form of vegetation; protect plants and surrounding areas from overspray.

Ensure adequate ventilation when applying Cromar Decking Sealer.

Application Temperature:

5°C or above

Drying Time:

The drying time will vary depending on the ambient temperature, climate conditions and porosity of the timber, but an average would be approximately 24 hours.

Container Sizes:

5 litres

Coverage Rates:

Coverage will vary dependent upon the properties of the substrate, but guideline coverage will be 6-8m²/litre.

Cleaning:

Brushes etc. can be cleaned using White Spirit removing as much Cromar Decking Sealer as possible before cleaning.

Storage Conditions:

Containers should be stored upright in a dry, cool and well-ventilated area away from direct sunlight and any sources of ignition.

Shelf Life:

Approximately 12 months if stored correctly.

Health&Safety:

Please refer to health and safety data sheet on Cromar Decking Sealer.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com