

# TECHNICAL DATA SHEET

## Double-Sided Vent3 Adhesive Tape

### DESCRIPTION:

Modified acrylic adhesive double-sided tape.

### USES:

To create air-tight laps between successive layers of Underlay/Vapour barrier membrane

### BENEFITS:

Easy to apply.  
Very high initial tack.  
High adhesion strength  
Provides extra reinforcement.  
Highly resistant to temperature changes over a wide range.  
Adheres to a very wide range of surfaces, including low energy substrates (e.g. PE, PP and non-woven materials).

### DIRECTIONS FOR USE:

Ensure surfaces are clean, dry and free from dust.  
Place underlay in correct position. Apply Tape to the lower lap.  
Place next lap in the required position and peel protective layer from tape.  
Join overlaps of underlay. Press join firmly to ensure good seal.

### TECHNICAL INFORMATION

• <b>Support</b>	PES/PVA scrim
• <b>Interliner</b>	Polyolefine foil, white, 80 µm
• <b>Adhesive weight</b>	155 g/m <sup>2</sup>
• <b>Total thickness</b>	0,15 mm
• <b>Temperature resistance</b>	from -40 °C to +80 °C
• <b>Adhesive strength</b>	min 24 N/25 mm
• (According to AFERA 5001)	Contact time: 1 h

### PACKAGING:

60mm wide x 25m roll (4 rolls per box)

### STORAGE

Store in unopened, original packaging between +5°C and +30°C in cool, dry conditions.

### Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.

**Further Information:**

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

[www.cromar.uk.com](http://www.cromar.uk.com)

Tel: 01977 663133 Fax: 01977 662186 E-mail: [info@cromar.uk.com](mailto:info@cromar.uk.com)