



# FIBRE-TORCH SAND-36KG FIBRE-TORCH GREEN-44KG

Issue 1 – November 2008

**Description:** Intended for use in built-up roofing as a top sheet or a torch-on for repair work. Using a traditional fibre based carrier, the membrane offers excellent application characteristics and activated bitumen flow at an economy price.

**Composition and Manufacture:** The base is formed from natural fibres bonded together to form an absorbent material core. The carrier material is saturated then coated both sides in a continuous operation using liquid oxidised bitumen. The coated material is finished with either fine sand or mineral flake as a top surface. A sanded selvedge is left along one edge of the mineral flake finish to ensure positive bonding of overlaps. The underside of the material is laminated with a plastic film, which burns off during torching and prevents sticking in the roll. The membrane is cut to roll length, wrapped and labelled according to specification.

**Performance Features:** Correctly installed, Fibre based torch-on membrane will give a long life in built up roofing systems. Membrane bonding is effected by flame torch allowing the optimum flow of bitumen during installation without the use of traditional equipment, giving ease of installation without waste. It can be cut and formed using sharp hand tools. Do not expose the membrane to hydrocarbon based solvent products.

**Storage and Handling:** Do not drag rolls across rough surfaces; they should be lifted. Rolls should be stood on their ends on a dry surface. If using pallets do not stack more than two pallets high. Avoid mechanical damage and damp storage conditions.

**Technical Data:**

Product	36KG	44KG
Carrier	Natural Fibre 400g/m <sup>2</sup>	Natural Fibre 400g/m <sup>2</sup>
Roll Size	10m x 1m	10m x 1m
Roll Weight	36kg	44kg
M <sup>2</sup>	3.6kg	4.4kg
Rolls Per Pallet	25	20

**Health and Safety:** Please refer to the Health And Safety Data Sheet on Fibre-Torch Sand 36kg and Fibre-Torch Green 44kg

**Further Information:** In the event of further queries or problems concerning the use of this product, please contact the address below:-  
All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar's products' are available for sale in accordance with Cromar's standard terms and conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.

Unit 3, The Maltings Industrial Estate  
Doncaster Road, Whitley Bridge  
North Yorkshire DN14 0HH  
Tel: 01977 663133 Fax: 01977 662186  
[info@cromar.uk.com](mailto:info@cromar.uk.com) [www.cromar.uk.com](http://www.cromar.uk.com)



**CROMAR**  
BUILDING PRODUCTS LIMITED