



GLASS PERFORATED MINERAL - 3G

Issue 4 – November 2008

Uses: Manufactured using a glass fibre tissue with oxidised bitumen. Intended for use in built-up felt roofing using traditional roll and pour bonding.

Storage and Handling: Do not drag rolls across rough surfaces, they should be lifted. Rolls should be stood on their ends on a dry surface. If using pallets do not stack more than two pallets high. Avoid mechanical damage and damp storage conditions.

Technical Performance Data (Typical)

Carrier:	Perforated Glass Tissue
Roll Size:	10m x 1m
Nominal Roll Weight	26kg
Nominal M ² Weight:	2.6 kg
Rolls Per Pallet:	30

Health & Safety: There are no harmful effects or Health + Safety Hazards related to Cromar Bonding Felts. However, we recommend that all installers observe and implement Health and Safety regulations in relation to the hot bonding material and heating equipment used.

Further Information: In the event of further queries or problems concerning the use of this product, please contact the address below:-

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar's products' are available for sale in accordance with Cromar's Standard Terms and Conditions of Sale, which are available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our Representatives, Agents, or Distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.

