

TECHNICAL DATA SHEET

MASONRY + DRY ROT FLUID

Issue 5 – October 2015

- Description:** Cromar Masonry + Dry Rot Fluid is a ready to use Fungicidal, Biocidal irrigation fluid.
- Use:** Water based fungicide and biocide compound for the treatment of masonry and brickwork, formulated to destroy and prevent re-infestation by wood rotting fungi, particularly dry rot - *Serpula Lacrymans*. Also recommended for the prevention and removal of moss, lichen and algae etc.
- Shake or stir container before using.
- Container Sizes:** 4, 25 and 200 litres
- Application Instructions:** Agitate material before use. Affected areas should be treated in depth by spraying or brushing liberally onto the surfaces. Wall of greater thickness than 4.5" should be drilled and irrigated.
- Coverage Rates:** Coverage will depend on the porosity of the substrate. Guideline coverage is 2-4m² per litre.
- Storage Life:** To ensure an airtight seal, replace lid immediately after use. Shelf life is indefinite if material is stored in a dry area at temperatures between 8°C and 25°C.
- Health & Safety:** Please refer to health and safety data sheet on Masonry + Dry Rot Fluid.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.