

TECHNICAL DATA SHEET

PATINATION OIL

Issue 1 – November 2015

- Description:** Specially developed to reduce unsightly staining and to impart a pleasing appearance to newly applied lead sheet and flashings.
- Preparation:** All lead to be treated should be clean, dry and free from dust and debris.
- Application:** Cromar Patination Oil should be applied after each step of the lead work, and completed by the end of the day.
Shake the container for at least 2 minutes prior to use.
Apply with a soft absorbent cloth, working horizontally and top to bottom.
Ensure the application is complete prior to any rain.
Do not allow Patination Oil to come into contact with bitumen and polycarbonate surfaces.
- Container Sizes:** 500ml, 1Lt & 2.5Lt
- Coverage Rates:** Approx. 60m² per litre
- Cleaning:** Brushes etc. can be cleaned with White Spirit followed by detergent.
- Storage Conditions:** Containers should be stored in a cool, dry, well ventilated place at between 5°C and 30°C
- Health & Safety:** Please refer to health and safety data sheet on Cromar Patination Oil

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.