

TECHNICAL DATA SHEET

ROOF & GUTTER SEALANT

Issue 5 – December 2012

Description:

Roof & Gutter Sealant is a gun applied, rubberised, oil based sealant intended for sealing joints in gutters, roofing sheets and other similar applications. The sealant is semi-drying product and remains predominantly in a semi dry, paste like condition. The nature of the product ensures excellent adhesion to most surfaces.

Application:

Roof & Gutter Sealant is intended for external weather sealing and because of its non-drying nature, is ideally suited for lap joints where it will maintain a weather proof seal, even in very thin sections when applied between two sheet material, which are mechanically fixed together.

Application Instructions:

All surfaces must be clean, dry and free from oil, grease or other contamination. Loose surface material should be removed by brushing. Powdery surfaces should be sealed with an alkaline resistant sealer. Roof & Gutter Sealant should not be used in constant water immersion situations. After use, tools should be cleaned with White Spirit or similar cleaner.

Technical Data:

Composition:	A blend of synthetic polymers and rubbers, processed oils and inorganic fillers.
Form:	Ready to use paste.
Specific Gravity:	1.70 – 1.78
Flashpoint:	>55°C
Application Temperature Range:	+5°C to +40°C
Service Temperature Range:	-10°C to +70°C
Slump Resistance:	Good, suitable for joints up to 15mm x 15mm
Service Life:	Up to 10 years when used as recommended
Shelf Life:	24 months in unopened containers stored under cool, dry conditions
Physical Change After Application:	The exposed surface of the sealant becomes tack-free a few days after application, while the bulk of the sealant remains in a pliable condition.

Coverage:

One cartridge is sufficient to produce 10.5m with a 6mm bead.

Storage:

Store in cool dry conditions

Health & Safety:

Please refer to health & safety data sheet on Roof & Gutter Sealant

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com