

TECHNICAL DATASHEET

Tech Seal Fibreglass Matting

Description & Uses

A high performance glass fibre chopped strand matting. The strands are bonded with a styrene-soluble emulsion binder.

Available in 1 metre wide rolls, 225gsm: 6.75kg, 11.25kg, 16.5kg, 33kg sizes.

Benefits

Tech Seal Fibreglass Matting has outstanding handling and moulding properties.

It is characterised by fast wet-out and wet-through, as well as easy air removal, which leaves a resin-rich surface.



Storage:

Tech Seal Fibreglass Matting should be stored in its original packing in a cool dry environment. Direct sunlight and sources of heat should be avoided.

Shelf Life:

12 months in original unopened packaging.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.