

TECHNICAL DATASHEET – Cromar Underlay Support tray

Description & Uses

Underlay support trays are essential components used in roofing systems to provide support and secure positioning for underlay membranes at the eaves of pitched roofs. They ensure that the underlay does not sag, preventing water ingress and maintaining proper ventilation.

Key Features and Benefits:

Material: High-density polyethylene (HDPE) or polypropylene (PP) for durability and weather resistance.

UV Stabilised: Protection against ultraviolet radiation to prevent degradation over time.

Ease of Installation: Lightweight design with pre-formed profiles for quick and secure fitting.

Ventilation: Designed to allow for proper air circulation, preventing condensation and moisture buildup.

Compatibility: Suitable for use with a wide range of roofing materials, including tiles, slates, and shingles.

Weatherproof: Resistant to extreme temperatures, ensuring performance in various climatic conditions.



Technical Specifications:

Length: 1.5 meters

Width: 235 mm

Dip width: 30mm and 50mm available.

Temperature Resistance: -40°C to +80°C.

Colour: Black

Standards Compliance: Complies with BS 5534 (Slating and Tiling for Pitched Roofs) and other relevant international standards.

Installation Instructions:

Preparation: Ensure the roof eaves are clean and free from debris.

Positioning: Lay the underlay support tray along the eaves, ensuring it overhangs the fascia board by approximately 10-15 mm.

Securing: Use roofing nails or screws to fix the tray securely to the roof structure at intervals of 300 mm.

Overlap: Overlap adjacent trays by at least 100 mm to ensure continuous support.

Underlay Placement: Lay the underlay membrane over the trays, ensuring it is securely fixed and free of wrinkles or gaps.

It is the user's responsibility to ensure suitability for use. Safety Data available on request. Read the label carefully prior to use.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com. All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.