

TECHNICAL DATA SHEET

WOOD TREATMENT

Decorative Wood Treatment for professionals and private End-users.

DESCRIPTION:

CROMAR WOOD TREATMENT is a liquid, pigmented stain for exterior use.

RANGE OF USE:

For all outside wood, that is not in direct contact to soil or surface water and not stressed statically. This includes e.g.: facades, carports, shutters and balcony railings. The product should not be used indoors.

BENEFITS:

The stain penetrates wood easily and thereby gets into inner layers. The pigmented product protects wood to a certain extent against the damaging effects of UV light and enhances its water repellency. After drying it is odourless. Natural grain and texture of the wood are accentuated.

DIRECTIONS FOR USE:

Wood surfaces must be clean and dry before treating.

New wood: No pre-treatment necessary.

Renovation: Remove all existing loose and defective coats (e.g. thick layer stains, clear or coloured top-coats). Do not breathe sanding dust.

Use only in well ventilated areas. Keep freshly treated wood roofed or otherwise protected against rain until completely dry.

The treatment is ready-to-use. Do not thin. Tighten cap and shake vigorously before, and during use.

Apply by brush, spreading out thinly and evenly along wood grain.

Not recommended for spraying applications.

Reseal container after use. Keep away from sources of ignition and do not smoke. Protect the environment (e.g. soil, plants, aquatic environment) from splashes. Do not apply in damp conditions or if rain is likely before drying is complete.

Application temp. : 10-30°C (wood and product).

Number of coats: 2-3 (depending on wood species)

Coverage: Effective at 140-180 ml/m²

Drying time: 12-24 h in normal conditions (20°C/65% rel. humidity). Low temperatures, increased humidity and ingredients of some wood types may increase drying time.

Cleaning of tools: Clean brushes with commercial brush cleaner or white spirit immediately after use.

STORAGE:

Store product in tightly closed original containers at temperatures below 30°C.

PACKAGING:

5lt and 25lt tins

COLOUR(S)

Dark brown, Light brown, Red cedar, Green, Rich Mahogany.

SHELF LIFE:

12 months From production date if stored as above.

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com