



ALL WEATHER SEALANT

Issue 4 - November 2008

- Description:** A universal Co-Polymer sealant that can be used for a wide range of sealing and weatherproofing applications around the home and in industry. Can be applied in wet weather.
- Uses:** Provides a superior adhesion to most surfaces such as glass, glazed surfaces, aluminium, lead and zinc can be used in building, glazing, roofing and ductwork applications and for emergency repairs in wet weather. Over paintable with most paints and stains.
- Colours:** Brown, White, Black, Clear, Grey
- Packaging:** 310ml cartridges packed 1 x 12
- Preparation:** All surfaces should be clean, and dust free.
- Application:** Gun sealant firmly into joint ensuring no air is trapped behind. If required place masking tape along joint edges, removing within 5 minutes of application.
- Finishing:** Always tool down using a spatula or stick wetted with soapy water within 5 minutes of application. Tack free in approximately 10 minutes. It is the user's responsibility to dispose of all packaging correctly.
- Limitations:** Among others not recommended for locations subject to continuous water emersion and not for aquaria, PE, PP and Teflon. If applied on bitumen or tar containing surfaces discolouration or change in properties can occur. Direct sun light and application temperatures above 30°C can cause blistering. Adhesion tests prior to the application are recommended. It is the users responsibility to determine suitability.

Technical Data:

Technical Data	Dimension	All Weather Sealant
Basis		S-EB-S
Application temperature	°C	+5/+40
Application rate 3mm/6,3bar	G/min	350
Flow ISO 7390	mm	3
Density	G/ml	0,95
Skin over time 23°C/55%RF	min	10
Frost resistant till -15°C during transport		yes
Shelf life between +5°C and +25°C	months	12
Paintable after curing		yes
solids	%	73
Joint movement capability	%	+15
Temperature resistance after curing	°C	-25/+80
Mechanical Properties		
2mm film		
Shore-A hardness (3s) DIN 53505		14
100% Modulus DIN 53504	Mpa (N/mm ²)	0,15
Tensile strength DIN 53504	Mpa (N/mm ²)	0,30
Elongation at break	%	300
Joint Dimensions		
Minimum joint width	4mm	
Maximum joint width	10mm	
Joint connection	4-8mm	6mm
	10mm	8mm





Technical Data Sheet

Quantity Estimator: Width x depth of joint x length (in linear metres) of joint, divide this by the volume of tube in ml= number of cartridges required.

Health and Safety: Please refer to the health and safety data sheet on All Weather Sealant.

Further Information: In the event of further queries or problems concerning the use of this product, please contact the address below:-

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.

Unit 3, The Maltings Industrial Estate
Doncaster Road, Whitley Bridge
North Yorkshire DN14 0HH
Tel: 01977 663133 Fax: 01977 662186
info@cromar.uk.com www.cromar.uk.com



CROMAR
BUILDING PRODUCTS LIMITED