

TECHNICAL DATA SHEET

ALUMINIUM PAINT (CONTRACTORS GRADE)

Issue 5 – January 2012

Description:

An economy version of Aluminium Paint – a bright aluminium, traditional, solar reflective coating suitable for application to bituminous roofing substrates.

Uses:

For the protection against sun and weathering of roofs, particularly where bituminous, exposed steel and corrugated iron surfaces are encountered.

Container Sizes:

1, 2.5, 5 & 25

Coverage Rates:

Approximately 5 – 10m² per litre per coat, depending upon the surface.

Drying Time:

Up to 72 hours dependent on the ambient temperature.

Method of Application:

By brush or airless spray.

Storage Conditions:

Store away from children. Containers must be kept sealed and stored under cover away from sources of heat and ignition. Do not allow water to contaminate the Aluminium Paint.

Storage Life:

12 months under good storage conditions in original unopened containers.

Application Instructions:

Surfaces should be clean, dry and free from dust and debris. Freshly applied bitumen coatings should be allowed to weather for at least 3 – 5 days prior to the application of Aluminium Paint (Contractors Grade). For use on Roofing Felt we recommend you prime the surface prior to applying the first coat of Aluminium Paint (Contractors Grade).

STIR THOROUGHLY BEFORE USE

Note: The appearance of a silver film on the surface of the paint after a short period of stirring does not signify that the paint is thoroughly uniform. It is advisable to stir for several minutes to ensure complete dispersion. Preference should be given to mechanical stirring. Two coats should be applied, the first being allowed to dry before application of the second. To avoid bronzing it is important that Aluminium Paint (Contractors Grade) is not applied too thickly. Do not brush excessively as this can cause softening of the substrate. The presence of moisture on the surface of rain falling before the Aluminium Paint (Contractors Grade) has dried can also cause bronzing. Do not use in temperatures less than +5°C.

Cleaning Tools:

Clean with White Spirit.

VOC Details:

EU Limit for this product CAT. 2(i) : 500g/l (2010). This product contains max. 410g/l VOC's

Health & Safety:

Please refer to health & safety data sheet on Aluminium Paint (Contractors Grade).

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com