

# TECHNICAL DATA SHEET

## ANTI CLIMB PAINT

Issue 5 – January 2012

### **Description:**

Cromar Anti Climb Paint is a thick single pack non-drying product of sticky nature, providing a slippery surface. Contains a hidden identifier.

### **Use:**

For use on window ledges, down pipes, gutters, walls and anywhere which may be used as a grip point to gain unauthorised access.

### **Surface Preparation:**

Ensure all surfaces are clean, dry and free from grease, oil and any other contaminants. Seal porous surfaces first. Roughen smooth surfaces using coarse abrasive paper or by wire brushing. Metal should be suitably prepared and primed prior to application. Any absorbent, bituminous or unpainted surfaces should also be suitably primed.

### **Application:**

Apply with a short haired brush or industrial mitt, smoothing to a uniform finish. It is most important that an effective thickness is applied (approx 0.5mm – 1mm, no more than this).

Do not thin – ready to use product. Wear suitable gloves and only apply to areas over arms reach (i.e over 1.8m or areas not subject to legitimate daily use). It is recommended that the presence of Cromar Anti Climb Paint operates best in areas where the temperature does not normally exceed 30°C. If applying in confined areas – ensure adequate ventilation.

### **Remarks:**

Notification signs should be used.

### **Container Sizes:**

4kg

### **Method of Application:**

By brush or mitt

### **Finish:**

Semi Matt

### **Coverage:**

1–2m<sup>2</sup> / kilo

0.5mm d.f.t (based on application by brush or mitt)

(The coverage rate may be lower as this depends on factors such as the porosity and roughness of the surface and material losses during application).

### **Storage:**

Store in a cool dry place, away from direct heat or naked flame. Containers should be tightly closed.

### **Cleaning:**

Brushes should be cleaned using White Spirit or Turps.

**VOC Content:**

144 g/litre

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

**Health & Safety:**

Please refer to Health & Safety Data Sheet for Anti Climb Paint

**Further Information:**

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com) or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

[www.cromar.uk.com](http://www.cromar.uk.com)

Tel: 01977 663133 Fax: 01977 662186 E-mail: [info@cromar.uk.com](mailto:info@cromar.uk.com)