

# TECHNICAL DATA SHEET

## CP PRIMER

Issue 2 – September 2016

### **Description:**

A vinyl acetate based primer specifically for preparing bituminous surfaces prior to over-laying with Cromar Cromapol. The products intended use is to prevent contamination of the Cromapol by a bitumen based substrate that could lead to adhesion failure of the coating.

### **Colour:**

Transparent Off-White Liquid.

### **Preparation:**

Care needs to be taken over preparation of surfaces before application.  
All surfaces must be clean, dry and free from oil, dirt, dust and loose debris.  
Any moss or mould must be removed using Cromar Moss and Mould Remover.

### **Method of Application:**

Two coats of CP Primer should be applied by brush, roller or squeegee to ensure an even coat with no pooling. It may also be applied evenly by airless spray.  
CP primer will dry within 1 hour under normal conditions.

### **Coverage:**

3 to 6 square metres per litre, per coat, dependent upon the nature of the surface.

### **Cleaning Tools:**

Tools may be cleaned with Methylated Spirit. Minor spillages should be wiped off surfaces immediately before the product has set. Major spillages should be mopped up immediately with an inert, absorbent material, such as sand and disposed of in accordance with local regulations.

### **Container Size:**

5 & 25Lt

### **VOC Details:**

EU Limit for this product CAT. 2(h) : 750g/l. This product contains max. 520g/l VOC's.

### **Storage:**

Containers must be kept sealed and stored away from sources of heat and ignition.

### **Shelf Life:**

12 months in undamaged, tightly sealed containers.

### **Health & Safety:**

Please refer to MSDS for CP Primer

### **Further Information:**

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com) or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which

is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

[www.cromar.uk.com](http://www.cromar.uk.com)

Tel: 01977 663133 Fax: 01977 662186 E-mail: [info@cromar.uk.com](mailto:info@cromar.uk.com)