

# TECHNICAL DATA SHEET

## CAPSHEET GREEN MINERAL

Issue 2 – October 2015

**Description:** Intended for use in built-up roofing as a top sheet. Using a traditional fibre based carrier, the membrane offers excellent application characteristics and is suitable in either repair applications or as part of built-up roofing.

**Composition and Manufacture:** The base is formed from natural fibres bonded together to form an absorbent material core. The carrier material is saturated then coated both sides in a continuous operation using liquid penetration and oxidised bitumen. The coated material is finished with a mineral flake as a top surface. A sanded selvedge is left along one edge of the mineral flake coating to ensure positive bonding of overlaps. The underside of the material is coated with sand.

**Testing Standards:** There is no specific British Standard for these materials.

**Performance Features:** Correctly installed, mineral felts will provide a long life to built-u roofing systems. The membrane is installed by using traditional hot bonding techniques described in BS Code of Practice 144 Part 3. It can be cut and formed using sharp hand tools.  
Do not expose the membrane to hydrocarbon based solvent products.

**Storage and Handling:** Do not drag rolls across rough surfaces, they should be lifted. Rolls should be stood on their ends on a dry surface. If using pallets do not stack more than two pallets high. Avoid mechanical damage and damp storage conditions.

**Technical Data:**

Product	Capsheet Green Mineral
Carrier	380gm/m <sup>2</sup> Rag Fibre
Roll Size	10m x 1m
Nominal Roll Weight	38kg
Nominal M <sup>2</sup> Weight	3.8kg
Rolls Per Pallet	25

**Health and Safety:** Please refer to the Health and Safety Data Sheet on Capsheet Green Mineral.

**Further Information:**

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

All products should be sold in accordance with the manufacturer’s instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products’ are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

[www.cromar.uk.com](http://www.cromar.uk.com)

Tel: 01977 663133 Fax: 01977 662186 E-mail: [info@cromar.uk.com](mailto:info@cromar.uk.com)