

DAP WATERTIGHT ROOF SEALANT

Issue 1 – February 2010

Description:

DAP Watertight Roof Sealant is a high performance, asphalt-based sealant. It is ideal for repairing minor roof leaks and preventing the penetration of air and moisture. It offers excellent adhesive and weathering features to outlast oil-based compounds. DAP Watertight Roof Sealant forms a long-lasting, watertight seal that resists cracking, crumbling and sagging. Can be used in wet applications (emergency roof repairs).

Suggested Uses:

Ideal for sealing:

- Corrugated Roofing
- Asphalt Surfaces
- Chimneys
- Roof/Pip Flashing
- Copings
- Gable Joints
- Shingles/Gutters
- Spotting Shingle Tabs
- Repairing Minor Roof Leaks

Adheres to:

- Wood
- Masonry
- Fibreglass
- Metal
- Asphalt

Performance Characteristics:

- Resists the damaging effects of ultra-violet light, temperature extremes and weathering that cause hardening, cracking and crumbling of oil-based sealants.
- Can be used for both wet and dry applications.
- Will not run or bubble.
- Forms a weather resistant, water-tight seal.
- Sets tack free in one hour. A full cure is attained in 2-4 weeks depending on temperature, humidity and depth of fill.

Surface Preparation & Application:

- Remove all old material from surface.
- Cut nozzle at 45° angle to desired bead size.
- Puncture inner foil seal.
- Load cartridge into conventional caulk gun.
- Fill cracks and gaps with sealant.
- DAP Watertight Roof Sealant sets tack free in less than one hour. A full set is attained in two to four weeks, depending on temperature, humidity and depth of fill.
- Paintable after one hour of application. However, we recommend using only high quality oil or asphalt based paint. One coat may show a slight discolouration. Two coats will provide a clean film.

For best results:

- Caulk in temperatures above 5°C.
- If joint should not exceed 3/8" x 3/8". If joint exceeds 3/8", use a polyethylene foam as a backer rod.
- Store caulk away from extreme heat or cold.

Physical & Chemical Characteristics:

Colour:	Black
Odour:	Asphaltic
Consistency:	Gun Grade
Vehicle:	Asphalt
Volatile:	Mineral Spirits
Pigment:	Inert Fillers
Flash Point:	38°C
Specific Gravity:	1.6
Solids:	86± 2% by Weight
Weight/Gallon:	13.5 lbs.
Application Temp:	5°C Minimum
Shelf Life:	1 Year minimum @ 21°C
Coverage:	56 linear feet at a 3/16 –inch bead
Packaging:	10.1 fl. Oz. Cartridges

Cleaning Tools:

Before setting, remove excess material with mineral spirits, After setting, excess material must be cut or scraped away.

Health and Safety:

Please refer to the Health and Safety Data Sheet on DAP Watertight Roof Sealant.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below:-

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar's products' are available for sale in accordance with Cromar's Standard Terms and Conditions of Sale, which are available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our Representatives, Agents, or Distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.