

TECHNICAL DATA SHEET

ELASTATEX REINFORCEMENT TAPE

Joint Reinforcement Tape

DESCRIPTION:

A butyl tape laminated with a non-woven polyester fleece.

AREAS OF USE:

Reinforcement of upstands, joints, cracks and gaps in flat roofs, in conjunction with Rapidcure Plus and Elasta-thane 25 systems.

BENEFITS:

Good adhesion to a wide range of substrates.
Remains flexible throughout its service life.
The product is highly conformable.
Easy and accurate to use with little waste and no mess.

DIRECTIONS FOR USE:

SURFACE PREPARATION

All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, it is recommended that acetone is used and allowed to dry prior to the application of the tape. When applying the tape to porous or friable surfaces, it is recommended that the surface be treated with a suitable primer, such as an exterior grade PVA, to seal and stabilise the surface.

APPLICATION

Remove the release paper and apply the tape to the substrates to be joined. Take care to avoid rucks in the tape. Roll the tape with a small roller to ensure good adhesion along the whole length of the tape. Application temperature range: +5°C to +40°C

PACKAGING:

100mm wide x 10m roll (8 per box)
150mm wide x 10m roll (4 per box)

COLOUR(S)

Grey

SHELF LIFE:

24 months when stored flat in original packaging in cool, dry conditions.

ADDITIONAL INFORMATION:

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com