

TECHNICAL DATA SHEET

FLEXIGLASS

Issue 1 – December 2017

Description:

Cromar Flexiglass is a pre-promoted thixotropic styrene free polyester flexible resin designed specifically for overlay Roofing Applications.

Benefits:

- Styrene free
- Overlay resin primer
- High flex resin properties
- Rapid cure system

Application:

For full application instructions please download the **FLEXIGLASS Installation Guide** from our website: -

<http://www.cromarbuildingproducts.com/>

Typical Properties:

Physical Data in Liquid State at 25°C:

Test	Units of Measure	Nominal
Viscosity; Brookfield LV3 @ 60 rpm	cps	1500
Thixotropic Index; 6/60	-	2.5
Monomer Content	%	25
Gel Time; 100g 2.5% catalyst L40 LV	minutes	20
Peak Exotherm	°C	100

Mechanical Data in the Cured State:

Storage:

Resins are stable for six months from date of production (3 months from point of sale) when stored in the original containers away from sunlight at no more than 21°C. After extended storage, some drift may occur in gel time.

During the hot summer months, no more than two months stability at 86°F/30°C should be anticipated.

Health & Safety:

Please refer to the Material Safety Data Sheet on Cromar **FLEXIGLASS**

Always read and understand the Material Safety Data Sheet before working with this product.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products'

are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Unit 3 The Maltings Industrial Estate, Doncaster Road, Whitley Bridge, North Yorkshire DN14 0HH

www.cromarbuildingproducts.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com