

# TECHNICAL DATA SHEET

## RENOCOAT ROOF TILE RENOVATION COAT

Issue 5 – November 2015

- Description:** Cromar Renocoat is a high quality 100% acrylic coating designed as a long lasting external decorative and protective finish for concrete and fibre cement roof tiles. The product has excellent durability and light-fast properties.
- Uses:** Suitable for use on concrete roof tiles. Excellent adhesion to porous surfaces. Cromar Renocoat should not be used on painted surfaces or high density/low suction substrates such as glazed brick and tiles, engineering bricks and natural slate tiles.
- Packaging:** 20 litres.  
5 litres.
- Preparation:** Clean the surface by power washing and/or brushing with a stiff brush. Replace broken or missing tiles and re-cement ridge/top tiles. Apply Cromar Moss & Mould Remover solution to prevent further fungal/algae growth. Apply two coats of Cromar Renocoat.
- Application:** Work should only be carried out in dry conditions, do not apply if rain is forecast within six hours of application and when the relative humidity level exceeds 90%. Do not apply in frosty conditions or when the substrate temperature is below 5° or above 35°C. Do not apply when the roof tile temperature is above 35° to ensure that no premature surface drying occurs. Cromar Renocoat may be applied by brush or airless sprayer. Do not thin prior to use, Cromar Renocoat will withstand rainfall after two hours in favourable drying conditions. Apply the first coat and leave to dry overnight before applying the second coat.
- Coverage:** The coverage rates will vary with roof profile and substrate porosity. The first coat application will give guideline coverage of 3-5m<sup>2</sup> per litre. The second coat application will be at a coverage rate of 7-10m<sup>2</sup> per litre.
- Cromar Fungicidal Wash should be applied at a rate of 6/8m<sup>2</sup> per litre.
- Cleaning Tools:** Clean all equipment immediately with water.
- Base:** Water Based.
- Surface Finish:** Matt.
- Health & Safety:** Please refer to health and safety data sheet on Water Based Roof Tile Renovation Coat.

### Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

[www.cromar.uk.com](http://www.cromar.uk.com)

Tel: 01977 663133 Fax: 01977 662186 E-mail: [info@cromar.uk.com](mailto:info@cromar.uk.com)