

TECHNICAL DATA SHEET

TEXTAPE

Self-Adhesive Scrim Tape

DESCRIPTION:

Self-adhesive fibreglass plasterboard joint tape for taping joints, repairing cracks and patching holes.

USES:

For reinforcing joints, crack repairs and hole patches in plaster/plasterboard/drywall walls and ceilings.

BENEFITS:

Easy to apply. High adhesion. Provides extra reinforcement.

DIRECTIONS FOR USE:

Ensure surfaces are clean, free from dust and dry. Peel required amount of tape and press firmly into place. Cut with a knife.

ADDITIONAL INFORMATION

Specification: 2.85 x 2.85mm (9 x 9 count/25cm)

Warp of yarn: 33texx2

Woof of yarn: 100tex

Mesh size: 9 x 9 mesh

Average of weight: $\geq 70\text{g/m}^2$

Tensile strength: Warp: 500n/50mm
Weft: 800n/50mm

Alkaline resistant acrylic and adhesive acrylic total content: 30 %

Alkaline resistant resin: acrylic resin.

Adhesive coating: acrylic resin. It will keep strong sticky within 6 months.

Alkaline resistance properties: after 28 days immersion of 5% NaOH solution, the average retention rate for tensile fracture strength $\geq 65\%$.

PACKAGING:

48mm x 90m

COLOUR(S)

White

STORAGE

Store in unopened, original packaging between +5°C and +30°C in cool, dry conditions.

Health & Safety

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 0GH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com