

TECHNICAL DATA SHEET

TROWEL MASTIC

Issue 6 – November 2015

Description:

Trowel Mastic is a heavily bodied bituminous mastic that is used for filling joints, cracks and splits in roofing and building materials including roofing felt, asphalt, concrete, asbestos cement and metallic guttering and drainpipes. It is resistant to water penetration immediately after application and is ideally suited for maintenance and remedial work.

Preparation:

Ensure that the surface is clean, dry and free from oil, grease, dirt and organic growth. Organic growth such as moss and lichen can be removed using Fungicidal Wash. Bolt heads on roof sheets should be wired brushed to remove rust before being sealed with Trowel Mastic. Porous surfaces should be primed with Bituminous Primer in order to seal the surface and allowed to dry thoroughly.

Method of Application:

In order to assist application, tools can be lubricated with white spirit or paraffin. Apply Trowel Mastic by trowel or putty knife, forcing material into cracks and joints and smoothing out on either side. Cracks or joints of more than 3mm should be reinforced with glass fibre scrim and covered with a second application of mastic.

Container Sizes:

1, 2.5, 5 & 25

Coverage Rates:

A typical coverage rate for a 2mm thickness of material is 2Lt/m². Drying time depends on weather conditions and film thickness. Heavy applications will result in extended drying times.

Storage Conditions/Shelf Life:

After use replace the lid to ensure an airtight seal. Shelf life is indefinite if container is kept sealed and is stored in a dry area at temperatures between 8°C and 25°C.

Cleaning Tools:

Clean with White Spirit.

VOC Details:

EU Limit for this product CAT. 2(i) : 500g/l (2010). This product contains max. 180g/l VOC's.

Health & Safety:

Please refer to health & safety data sheet on Trowel Mastic.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, or e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and

accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,5 Northside Industrial Estate, Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com