

TECHNICAL DATA SHEET

WETBOND

Issue 2 – July 2013

Description:

Wetbond is a bitumen based roofing compound.

Advantages:

Incorporates a polymer adhesion additive
An Ideal emergency repair material
Impermeable to water immediately after application
May be applied to wet surfaces
Provides a fine textured weatherproof coating.

Suitability:

Suitable for use on existing pitched or flat roofs, slate, tiles, steel, concrete, stone, cast iron, aluminium asphalt and timber.

Colour:

Black

Coverage:

1 – 1.5 m² per litre on average.

Surface Preparation:

The surface must be sound and free of loose or friable materials, rust, fungus, mould and lichens prior to application.

Application:

Wetbond may be applied by brush to all surfaces even during or immediately after heavy rainfall. It may also be applied under water. The coating will only begin to dry when surface water has evaporated.

Apply two coats allowing the first coat to dry before application of the second coat.

Container Sizes:

25 ltrs

Flashpoint:

50°C

Storage:

Wetbond should be stored indoors between 5°C - 20°C away from sources of ignition and naked flames etc. Store away from children.

Health & Safety:

Please refer to health & safety data sheet on Wetbond.

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com or telephone our Technical Line on 0844 8588186:

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.



Units 3,4,&5 Northside Industrial Park , Whitley Bridge, North Yorkshire DN14 OGH

www.cromar.uk.com

Tel: 01977 663133 Fax: 01977 662186 E-mail: info@cromar.uk.com