BITUMEN PRIMER

Page: 1

Compilation date: 20/08/2016

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BITUMEN PRIMER

Product code: 521

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name:	Cromar Building	Products Ltd
---------------	-----------------	--------------

Units 3, 4 & 5 Northside Industrial Park

Selby Road

Whitley Bridge

North Yorkshire

DN14 0GH

United Kingdom

Tel: 01977663133

Fax: 01977662186

Email: sales@cromar.uk.com

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

	STOT RE 1: H372; Asp. Tox. 1: H304; Flam. Liq. 3: H226 Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes
·	damage to organs through prolonged or repeated exposure.

2.2. Label elements

Label elements:

 Hazard statements:
 H226: Flammable liquid and vapour.

 H304: May be fatal if swallowed and enters airways.

 H372: Causes damage to organs through prolonged or repeated exposure.

 GHS02: Flame

 GHS08: Health hazard



BITUMEN PRIMER

Precautionary statements:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P241: Use explosion-proof electrical/ventilating/lighting/ equipment.
	P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
	P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-185-4	64742-82-1	-	STOT RE 1: H372; Asp. Tox. 1: H304	50-70%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

BITUMEN PRIMER

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of

the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:Store in a cool, well ventilated area. Keep container tightly closed. Keep away from
sources of ignition. Prevent the build up of electrostatic charge in the immediate area.
Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

BITUMEN PRIMER

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Black		
Odour:	Aromatic		
Evaporation rate:	Moderate		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Insoluble		
Also soluble in:	Most organic solvents.		
Viscosity:	Non-viscous		
Boiling point/range°C:	153 F	lammability limits %: lower:	No data available.
upper:	No data available.	Flash point°C:	39
Part.coeff. n-octanol/water:	No data available.	Autoflammability°C:	No data available.
Relative density:	0.916	pH:	Approx. 7
VOC g/l:	450		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

BITUMEN PRIMER

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for product:

Hazard	Route	Basis
STOT-repeated exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

BITUMEN PRIMER

13.1. Waste treatment methods

		_
Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal	
	company.	
NB:	The user's attention is drawn to the possible existence of regional or national	
	regulations regarding disposal.	
Section 14: Transport informa	tion	
14.1. UN number		1
UN number:	11N1262	
		1
14.2. UN proper shipping name		
	PAINT RELATED MATERIAL	_
14.3. Transport hazard class(e	s)	
Transport class:	3	
14.4. Packing group		
Packing group:	III	
14.5. Environmental hazards		
Environmentally hazardous:	No Marine pollutant: No	
14.6. Special precautions for u	ser]
Special precautions:	No special precautions.	
Tunnel code:		
Transport category:	3	
Section 15: Regulatory inform	ation	
15.1. Safety health and enviro	nmental regulations/legislation specific for the substance or mixture	1
Specific regulations:		٦
15.2. Chemical Safety Assessr	nent	
Chemical safety assessment:	A chemical safety assessment has not been carried out for the substance or the mixture	
	by the supplier.	
Section 16: Other information		
Other information		1
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	-
	2015/830.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H226: Flammable liquid and vapour.	
	H304: May be fatal if swallowed and enters airways.	
	H372: Causes damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through</or>	
	Icont	1

BITUMEN PRIMER

Page: 7

prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.