

# TECHNICAL DATASHEET

## Line Marking Paint

### Description & Uses

A solvent based, spray applied, line marking paint – quick drying (30 minutes) and semi permanent. Ideal for spot marking for contractors on roads, factory and warehousing floors etc as well as for grass applications.

Suitable for use on various substrates, will last at least 3 months under normal wear and tear.

Available in a range of colours including; White, Red, Yellow and Blue.

### Directions

- Use in a well-ventilated area.
- Shake can well before use for 2 to 3 minutes so that it rattles.
- Remove the cap and turn the can upside down.
- For hand use point the can in the required direction, depress the nozzle with one finger on either side of the button. (Alternatively, the aerosol can be inserted into a line marking machine, then tighten and press the trigger to get a spray.)
- Do not allow the paint to dry in the nozzle. Clear by turning the can so it points upwards and press the nozzle for a few seconds until clear.

### Storage

Protect from extremes of temperature in a controlled environment between 5 and 25°C, and away from direct sunlight. **Do not stand on a cold concrete floor. Do not allow the product to freeze.**

### Shelf Life

12 months when stored in original, unopened packaging.

### Limitations

- Do not apply in wet weather, or if rain is impending.
- When applying on roads or car parks, allow to dry for 2 hours before trafficking.
- Do not use below 3°C or when humidity is over 90%.
- It is the user's responsibility to ensure suitability for use.
- **Read the label carefully prior to use it contains essential health and safety information, further details can be found on the Safety Data Sheet.**



### Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

*All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.*