

# TECHNICAL DATASHEET

## Floor Defence Contract Hard Surface Protector

### Description & Uses

AlphaChem, from Cromar, introduce Floor Defence a clear multi-purpose, contractors grade, self adhesive floor protector.

Ideal for providing a superior level of protection on all types of hard surfaces, including timber, hardwood, ceramic, vinyl, laminate, stone floors and worktops, from potentially expensive damage and spills – the perfect partner for any decorating, DIY or building work.

Floor Defence provides a safer alternative to dust sheets, which can be a trip hazard, and is easy to apply without the need for a special applicator. And being reverse wound the rolls are easy to apply, can be left down for up to 28 days, and are easily removed once a job is finished, leaving no adhesive residue behind.

- Ideal for all types of hard surfaces
- Protects against spills and damage
- Leaves no residue
- Reverse wound for ease of application
- No applicator required
- Easy to apply and remove

### Directions

- Ensure all surfaces are clean, sound, dry and free from dust, oil, solvents or other chemicals.
- Simply unwrap the roll, pull out a short length and place (sticky side down) on the surface to protect.
- Unwind the roll, ensuring adhesion to the surface as you go, and cut off the product with a knife when the edge of the surface is reached.
- Take care to remove Floor Defence within 28 days of application.

### Shelf Life

36 months from manufacture date.

### Storage

Store indoors in cool, dry conditions +5 to +25°C.



### Limitations

- Do not leave down from more than 28 days.
- Always test a small inconspicuous area for adhesion compatibility before large scale use.
- Not recommended for outdoor use.
- Adhesive is not water resistant.
- Do not use on substrates which bleed oils or plasticisers.
- Not suitable for use in areas where underfloor is in use.
- Not suitable for use on carpets and textiles, use AlphaChem Floor Defence Carpet Protector.
- On some surfaces a residue may be left, this can easily be removed using AlphaChem Grafters Wipes or a specialist hard surface cleaner.
- If applied in heavily trafficked areas or temperatures in excess of 22°C, remove after 1 week maximum.
- It is the user's responsibility to determine suitability for use.

### Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail [info@cromar.uk.com](mailto:info@cromar.uk.com).

*All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.*