

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: AlphaChem All Weather Adhesive
Product code	: X1WEA
Type of product	: Paste
Product group	: Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Consumer use, Professional use, Industrial use
Use of the substance/mixture	: Multipurpose adhesive and filler for use in all weathers and with most substrates
Use of the substance/mixture	: Adhesives, binding agents
Function or use category	: Adhesives, binding agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Cromar Building Products
Units 3, 4, 5 Northside Ind Park
Selby Rd
DN14 0GH Whitley Bridge - United Kingdom
T 01977 663133 - F 01977 662186
www.cromarbuildingproducts.com

1.4. Emergency telephone number

Emergency number : 01977 663133 (Business hours only Mon-Fri 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Acute toxicity (inhalation:dust,mist) Category 1	H330
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Full text of H statements : see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Warning

Hazardous ingredients

: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]; n-butyl acetate

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H330 - Fatal if inhaled.
H336 - May cause drowsiness or dizziness.

AlphaChem All Weather Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P284 - Wear respiratory protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 - Immediately call a POISON CENTER or doctor. P312 - Call a POISON CENTRE or doctor if you feel unwell. P320 - Specific treatment is urgent (see supplemental first aid instruction on this label). P370+P378 - In case of fire: Use media other than water to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8	30 - 35	Carc. 1B, H350
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1	20 - 26	Flam. Liq. 3, H226 STOT SE 3, H336
Bis (2,2,6,6-tetramethyl-4-piperidyl) sebacate	(CAS-No.) 52829-07-9 (EC-No.) 258-207-9 (REACH-no) 01-2119537297-XXXX	0.1 - 0.2	Eye Dam. 1, H318 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Cough. May cause drowsiness or dizziness. May cause headache, nausea and irritation of respiratory tract.
Symptoms/effects after skin contact	: May cause moderate irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting.

AlphaChem All Weather Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO₂, dry sand, or alcohol-resistant foam. Water spray.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.
Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Precautionary measures fire : Eliminate all ignition sources if safe to do so. This product is not to be used under conditions of poor ventilation. Keep container closed when not in use.
Protection during firefighting : Wear recommended personal protective equipment. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes.

6.1.1. For non-emergency personnel

Protective equipment : EN 133.
Emergency procedures : Avoid contact with skin, eyes and clothing. Do not breathe vapours. Keep upwind. Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Breathing apparatus. EN 133. Wear recommended personal protective equipment.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation. Take up liquid spill into absorbent material, e.g.: sand. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Ensure good ventilation of the work station. Ground/bond container and receiving equipment. Keep only in original container. Use personal protective equipment as required. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharge. Keep in a cool, well-ventilated place away from heat.
Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Keep only in original container.
Incompatible products : Oxidizing agent. Strong acids. Strong bases.
Incompatible materials : Sources of ignition.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

AlphaChem All Weather Adhesive		
United Kingdom	Local name	n-Buty lacetate
United Kingdom	WEL TWA (mg/m ³)	724 mg/m ³

AlphaChem All Weather Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

AlphaChem All Weather Adhesive		
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m ³)	966 fibers/mL
United Kingdom	WEL STEL (ppm)	200 ppm

n-butyl acetate (123-86-4)		
EU	Local name	n-butyl acetate
EU	Notes	(Ongoing)
EU	Regulatory reference	SCOEL Recommendations
United Kingdom	Local name	Butyl acetate
United Kingdom	WEL TWA (mg/m ³)	724 mg/m ³
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m ³)	966 mg/m ³
United Kingdom	WEL STEL (ppm)	200 ppm
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

AlphaChem All Weather Adhesive

DNEL/DMEL (Workers)

Acute - systemic effects, dermal	11 mg/kg bw/day n-butylacetate
Acute - systemic effects, inhalation	600 mg/m ³ n-Butylacetate
Long-term - systemic effects, dermal	11 mg/kg bw/day
Long-term - systemic effects, inhalation	300 mg/m ³ n-Butylacetate

DNEL/DMEL (General population)

Acute - systemic effects, inhalation	300 mg/m ³ n-Butylacetate
Acute - systemic effects, oral	2 ng/kg bodyweight/day
Acute - local effects, dermal	6 mg/kg bw/day
Long-term - systemic effects, oral	2 mg/kg bw/day n-Butylacetate
Long-term - systemic effects, dermal	6 mg/kg bw/day n-butylacetate
Long-term - local effects, dermal	no effect

PNEC (Water)

PNEC aqua (freshwater)	0.18 mg/l n-Butylacetate
PNEC aqua (marine water)	0.018 mg/l n-Butylacetate
PNEC aqua (intermittent, freshwater)	0.36 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	0.981 mg/l n-Butylacetate
PNEC sediment (marine water)	0.0981 mg/l

PNEC (Soil)

PNEC soil	0.0903 mg/kg dwt n-Butylacetate
-----------	---------------------------------

PNEC (STP)

PNEC sewage treatment plant	35.6 mg/l n-Butylacetate
-----------------------------	--------------------------

8.2. Exposure controls

Appropriate engineering controls:
Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment:
Wear recommended personal protective equipment.

Hand protection: protective gloves
--

AlphaChem All Weather Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR), Butyl rubber, Polyvinylchloride (PVC)	3 (> 60 minutes)	0.3		EN 374-3

Eye protection:

Chemical goggles or safety glasses

Type	Use	Characteristics	Standard
Safety goggles, Safety glasses		With side shields	EN 166

Skin and body protection:

Long sleeved protective clothing. Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Device	Filter type	Condition	Standard
Gas filters	Type A - High-boiling (>65 °C) organic compounds	Vapour protection	EN 143

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various.
Odour	: characteristic.
Odour threshold	: 7 - 20 ppm n-Butylacetate
pH	: 6.2
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 126 °C Based on n-Butylacetate
Flash point	: 27 °C vapour
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 15 mbar
Relative vapour density at 20 °C	: 4
Relative density	: 0.93 g/cm ³
Solubility	: Water: not soluble
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 15000 mPa.s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 24 %
-------------	--------

AlphaChem All Weather Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Stable under normal conditions of use. Liquids/vapours may ignite or react with other materials.

10.4. Conditions to avoid

Avoid formation of vapours.

10.5. Incompatible materials

Strong bases. Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:dust,mist: Fatal if inhaled.

AlphaChem All Weather Adhesive	
LD50 oral rat	10760 mg/kg n-Butylacetate
LD50 oral	> 5000 mg/kg petroleum
LD50 dermal rat	> 14000 mg/kg
LC50 inhalation rat (mg/l)	23.4 ppb
ATE CLP (vapours)	0.023 mg/l/4h
ATE CLP (dust,mist)	0.023 mg/l/4h

Skin corrosion/irritation : Not classified
pH: 6.2
Serious eye damage/irritation : Not classified
pH: 6.2
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified
Chronic aquatic toxicity : Not classified

AlphaChem All Weather Adhesive	
LC50 fish 1	18 mg/l n-Butylacetate
EC50 Daphnia 1	44 mg/l n-Butylacetate

12.2. Persistence and degradability

AlphaChem All Weather Adhesive	
Persistence and degradability	% biodegradation.
Biodegradation	83 % aerobic, based on n-Butylacetate

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

AlphaChem All Weather Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code	: 15 01 10* - packaging containing residues of or contaminated by dangerous substances 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN


ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1133	1133	1133	1133	1133
14.2. UN proper shipping name				
ADHESIVES	ADHESIVES	Adhesives	ADHESIVES	ADHESIVES
Transport document description				
UN 1133 ADHESIVES, 3, III, (D/E)	UN 1133 ADHESIVES, 3, III	UN 1133 Adhesives, 3, I	UN 1133 ADHESIVES, 3, I	UN 1133 ADHESIVES, 3, I
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	I	I	I
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No

No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: 3YE

AlphaChem All Weather Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport by sea

Special provisions (IMDG)	: 223, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

Air transport

PCA Excepted quantities (IATA)	: E3
PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 351
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 361
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 500 ml
Excepted quantities (ADN)	: E3
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F1
Excepted quantities (RID)	: E3
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP7, MP17
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP27
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 1
Hazard identification number (RID)	: 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

VOC content : 24 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

AlphaChem All Weather Adhesive

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:	
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product